



# SCH1334

## P-Channel Power MOSFET -12V, -1.6A, 215mΩ, Single SCH6

ON Semiconductor®

<http://onsemi.com>

### Features

- Low ON-resistance
- High-speed switching
- 1.8V drive
- Halogen free compliance
- Protection diode in

### Specifications

#### Absolute Maximum Ratings at Ta=25°C


Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V <sub>DSS</sub>		-12	V
Gate-to-Source Voltage	V <sub>GSS</sub>		±10	V
Drain Current (DC)	I <sub>D</sub>		-1.6	A
Drain Current (Pulse)	I <sub>DP</sub>	PW≤10μs, duty cycle≤1%	-6.4	A
Allowable Power Dissipation	P <sub>D</sub>	When mounted on ceramic substrate (900mm <sup>2</sup> ×0.8mm)	0.8	W
Channel Temperature	T <sub>ch</sub>		150	°C
Storage Temperature	T <sub>stg</sub>		-55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

### Package Dimensions

unit : mm (typ)


7028-002



### Product & Package Information

- Package : SCH6
- JEITA, JEDEC : SOT-563
- Minimum Packing Quantity : 5,000 pcs./reel


### Packing Type : TL



### Marking




### Electrical Connection



## Electrical Characteristics at Ta=25°C









Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	V(BR)DSS	ID=-1mA, VGS=0V	-12			V
Zero-Gate Voltage Drain Current	IDS	VDS=-12V, VGS=0V			-10	μA
Gate-to-Source Leakage Current	IGSS	VGS=±8V, VDS=0V			±10	μA
Cutoff Voltage	VGS(off)	VDS=-6V, ID=-1mA	-0.4		-1.3	V
Forward Transfer Admittance	yfs	VDS=-6V, ID=-0.8A	1.2	2.1		S
Static Drain-to-Source On-State Resistance	RDS(on)1	ID=-0.8A, VGS=-4.5V		165	215	mΩ
	RDS(on)2	ID=-0.4A, VGS=-2.5V		245	345	mΩ
	RDS(on)3	ID=-0.1A, VGS=-1.8V		370	560	mΩ
Input Capacitance	Ciss	VDS=-6V, f=1MHz		120		pF
Output Capacitance	Coss			46		pF
Reverse Transfer Capacitance	Crss			36		pF
Turn-ON Delay Time	t <sub>d(on)</sub>	See specified Test Circuit.		4.9		ns
Rise Time	t <sub>r</sub>			17.5		ns
Turn-OFF Delay Time	t <sub>d(off)</sub>			16.0		ns
Fall Time	t <sub>f</sub>			16.5		ns
Total Gate Charge	Qg	VDS=-6V, VGS=-4.5V, ID=-1.6A		1.6		nC
Gate-to-Source Charge	Qgs			0.27		nC
Gate-to-Drain "Miller" Charge	Qgd			0.43		nC
Diode Forward Voltage	VSD	I <sub>S</sub> =-1.6A, VGS=0V		-0.88	-1.2	V




## Switching Time Test Circuit



## Ordering Information

Device	Package	Shipping	memo
SCH1334-TL-H	SCH6	5,000pcs./reel	Pb Free and Halogen Free






## Taping Specification

SCH1334-TL-H


## 1. Packing Format

Package Name	Carrier Tape Type	Maximum Number of devices contained (pcs)			Packing format	
		Reel	Inner box	Outer box	Inner BOX (C-1)	Outer BOX (A-7)
SCH6	SCH6	5,000	25,000	150,000	5 reels contained Dimensions:mm (external) 183×72×185	6 inner boxes contained Dimensions:mm (external) 440×195×210




## 2. Taping configuration

## 2-1. Carrier tape size (unit:mm)




## 2-2. Device placement direction




Those with pin 1 index on the feed hole side.....TL

## Outline Drawing

SCH1334-TL-H



## Land Pattern Example



Note on usage : Since the SCH1334 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.