

NTUD3127C

Small Signal MOSFET

**20 V, 200 mA / -180 mA, Complementary,
1.0 x 1.0 mm SOT-963 Package**

Features

- Complementary MOSFET Device
- 1.5 V Gate Voltage Rating
- Ultra Thin Profile (< 0.5 mm) Allows It to Fit Easily into Extremely Thin Environments such as Portable Electronics.
- These are Pb-Free Devices

Applications

- Load Switch with Level Shift
- Optimized for Power Management in Ultra Portable Equipment

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter			Symbol	Value	Unit	
Drain-to-Source Voltage			V_{DSS}	20	V	
Gate-to-Source Voltage			V_{GS}	± 8	V	
N-Channel Continuous Drain Current (Note 1)	Steady State	$T_A = 25^\circ\text{C}$	I_D	160	mA	
		$T_A = 85^\circ\text{C}$		115		
	$t \leq 5 \text{ s}$	$T_A = 25^\circ\text{C}$		200		
		$T_A = 85^\circ\text{C}$		-140		
	$t \leq 5 \text{ s}$	$T_A = 25^\circ\text{C}$		-100		
		$T_A = 85^\circ\text{C}$		-180		
P-Channel Continuous Drain Current (Note 1)	Steady State	$T_A = 25^\circ\text{C}$	P_D	125	mW	
		$T_A = 85^\circ\text{C}$		200		
	$t \leq 5 \text{ s}$	$T_A = 25^\circ\text{C}$		800		
Power Dissipation (Note 1)	Steady State	$T_A = 25^\circ\text{C}$	I_{DM}	-600	mA	
		$t \leq 5 \text{ s}$		200		
Pulsed Drain Current	N-Channel	$t_p = 10 \mu\text{s}$	I_{DM}	800	mA	
	P-Channel			-600		
Operating Junction and Storage Temperature			T_J, T_{STG}	-55 to 150	°C	
Source Current (Body Diode) (Note 2)			I_S	200	mA	
Lead Temperature for Soldering Purposes (1/8" from case for 10 s)			T_L	260	°C	

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Surface-mounted on FR4 board using the minimum recommended pad size, 1 oz. Cu.
2. Pulse Test: pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$




ON Semiconductor®

<http://onsemi.com>

$V_{(BR)DSS}$	$R_{DS(on)} \text{ Max}$	$I_D \text{ Max}$
P-Channel -20 V	5.0 Ω @ -4.5 V	-0.18 A
	7.0 Ω @ -2.5 V	
	10 Ω @ -1.8 V	
	14 Ω @ -1.5 V	
N-Channel 20 V	3.0 Ω @ 4.5 V	0.20 A
	4.0 Ω @ 2.5 V	
	6.0 Ω @ 1.8 V	
	10 Ω @ 1.5 V	

PINOUT: SOT-963



MARKING DIAGRAM



S = Specific Device Code
M = Date Code

ORDERING INFORMATION

Device	Package	Shipping [†]
NTUD3127CT5G	SOT-963 (Pb-Free)	8000 / Tape & Reel

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction-to-Ambient – Steady State, Minimum Pad (Note 3)	$R_{\theta JA}$	1000	°C/W
Junction-to-Ambient – $t \leq 5$ s (Note 3)		600	

3. Surface-mounted on FR4 board using the minimum recommended pad size, 1 oz. Cu.

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	N/P	Test Condition	Min	Typ	Max	Unit
-----------	--------	-----	----------------	-----	-----	-----	------

OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	N	$V_{GS} = 0$ V	$I_D = 250$ μA	20			V
		P		$I_D = -250$ μA	-20			
Zero Gate Voltage Drain Current	I_{DSS}	N	$V_{GS} = 0$ V, $V_{DS} = 5.0$ V	$T_J = 25^\circ C$			50	nA
		P		$T_J = 85^\circ C$			200	
		N	$V_{GS} = 0$ V, $V_{DS} = -5.0$ V	$T_J = 25^\circ C$			-50	
		P		$T_J = 85^\circ C$			-200	
Zero Gate Voltage Drain Current	I_{DSS}	N	$V_{GS} = 0$ V, $V_{DS} = 16$ V	$T_J = 25^\circ C$			100	nA
		P	$V_{GS} = 0$ V, $V_{DS} = -16$ V				-100	
Gate-to-Source Leakage Current	I_{GSS}	N	$V_{DS} = 0$ V, $V_{GS} = \pm 5.0$ V				100	nA
		P					-100	

ON CHARACTERISTICS (Note 4)

Gate Threshold Voltage	$V_{GS(TH)}$	N	$V_{GS} = V_{DS}$	$I_D = 250$ μA	0.4		1.0	V
		P		$I_D = -250$ μA	-0.4		-1.0	
Drain-to-Source On Resistance	$R_{DS(on)}$	N	$V_{GS} = 4.5$ V, $I_D = 100$ mA			1.5	3.0	Ω
		P	$V_{GS} = -4.5$ V, $I_D = -100$ mA			4.0	5.0	
		N	$V_{GS} = 2.5$ V, $I_D = 50$ mA			2.0	4.0	
		P	$V_{GS} = -2.5$ V, $I_D = -50$ mA			5.0	7.0	
		N	$V_{GS} = 1.8$ V, $I_D = 20$ mA			3.0	6.0	
		P	$V_{GS} = -1.8$ V, $I_D = -20$ mA			6.5	10	
		N	$V_{GS} = 1.5$ V, $I_D = 10$ mA			4.0	10	
		P	$V_{GS} = -1.5$ V, $I_D = -10$ mA			7.5	14	
		N	$V_{GS} = 1.2$ V, $I_D = 1.0$ mA			5.5		
		P	$V_{GS} = -1.2$ V, $I_D = -1.0$ mA			11.5		
Forward Transconductance	g_{FS}	N	$V_{DS} = 5.0$ V, $I_D = 125$ mA			0.35		S
		P	$V_{DS} = -5.0$ V, $I_D = -125$ mA			0.26		

CHARGES, CAPACITANCES AND GATE RESISTANCE

Input Capacitance	C_{ISS}	N	$f = 1$ MHz, $V_{GS} = 0$ V $V_{DS} = 15$ V		9.0		pF
Output Capacitance	C_{OSS}				3.0		
Reverse Transfer Capacitance	C_{RSS}				2.2		
Input Capacitance	C_{ISS}	P	$f = 1$ MHz, $V_{GS} = 0$ V $V_{DS} = -15$ V		12		
Output Capacitance	C_{OSS}				2.7		
Reverse Transfer Capacitance	C_{RSS}				1.0		

4. Switching characteristics are independent of operating junction temperatures

NTUD3127C

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	N/P	Test Condition		Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS, $V_{GS} = 4.5 \text{ V}$ (Note 4)								
Turn-On Delay Time	$t_{d(\text{ON})}$	N	$V_{GS} = 4.5 \text{ V}, V_{DD} = 10 \text{ V}, I_D = 200 \text{ mA}, R_G = 2.0 \Omega$		15			ns
Rise Time	t_r				24			
Turn-Off Delay Time	$t_{d(\text{OFF})}$				90			
Fall Time	t_f				60			
Turn-On Delay Time	$t_{d(\text{ON})}$	P	$V_{GS} = -4.5 \text{ V}, V_{DD} = -15 \text{ V}, I_D = -180 \text{ mA}, R_G = 2.0 \Omega$		20			
Rise Time	t_r				37			
Turn-Off Delay Time	$t_{d(\text{OFF})}$				112			
Fall Time	t_f				97			

DRAIN-SOURCE DIODE CHARACTERISTICS

Forward Diode Voltage	V_{SD}	N	$V_{GS} = 0 \text{ V}, I_S = 10 \text{ mA}$	$T_J = 25^\circ\text{C}$		0.60	1.0	V
		P	$V_{GS} = 0 \text{ V}, I_S = -10 \text{ mA}$			-0.65	-1.0	

4. Switching characteristics are independent of operating junction temperatures

TYPICAL PERFORMANCE CURVES – N-CHANNEL




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL PERFORMANCE CURVES – N-CHANNEL




Figure 7. Capacitance Variation




Figure 8. Resistive Switching Time Variation vs. Gate Resistance




Figure 9. Diode Forward Voltage vs. Current

TYPICAL PERFORMANCE CURVES – P-CHANNEL




Figure 10. On-Region Characteristics




Figure 11. Transfer Characteristics




Figure 12. On-Resistance vs. Gate Voltage




Figure 13. On-Resistance vs. Drain Current and Gate Voltage




Figure 14. On-Resistance Variation with Temperature




Figure 15. Drain-to-Source Leakage Current vs. Voltage

TYPICAL PERFORMANCE CURVES – P-CHANNEL




Figure 16. Capacitance Variation




Figure 17. Resistive Switching Time Variation vs. Gate Resistance





Figure 18. Diode Forward Voltage vs. Current

PACKAGE DIMENSIONS

SOT-963
CASE 527AA-01
ISSUE D




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.40	0.45	0.50	0.016	0.018	0.020
b	0.10	0.15	0.20	0.004	0.006	0.008
C	0.05	0.10	0.15	0.002	0.004	0.006
D	0.95	1.00	1.05	0.037	0.039	0.041
E	0.75	0.80	0.85	0.03	0.032	0.034
e	0.35 BSC			0.014 BSC		
L	0.05	0.10	0.15	0.002	0.004	0.006
H_E	0.95	1.00	1.05	0.037	0.039	0.041

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free

USA/Canada

Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910

Japan Customer Focus Center

Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.comOrder Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative