

Silicon Bridge Rectifier

V_{RRM} = 50 V - 1000 V
I_F = 4 A

Features

- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- High surge current capability
- Reliable low cost construction utilizing molded plastic technique
- Silver plated copper leads

KBL Package

Mechanical Data

Case: Molded plastic



Weight: 0.167 oz, 5 g

Mounting position: Any

Terminals: Plated leads, solderable per MIL-STD-202F,
Method 208

Polarity: Marked on body

Maximum ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	KBL401G	KBL402G	KBL403G	KBL404G	Unit
Repetitive peak reverse voltage	V _{RRM}		50	100	200	400	V
RMS reverse voltage	V _{RMS}		35	70	140	280	V
DC blocking voltage	V _{DC}		50	100	200	400	V
Continuous forward current	I _F	T _C ≤ 50 °C	4	4	4	4	A
Surge non-repetitive forward current, Half Sine Wave	I _{F,SM}	T _C = 25 °C, t _p = 8.3 ms	120	120	120	120	A
Operating temperature	T _j		-50 to 150	-50 to 150	-50 to 150	-50 to 150	°C
Storage temperature	T _{stg}		-50 to 150	-50 to 150	-50 to 150	-50 to 150	°C

Electrical characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	KBL401G	KBL402G	KBL403G	KBL404G	Unit
Diode forward voltage	V _F	I _F = 4 A, T _j = 25 °C	1.1	1.1	1.1	1.1	V
Reverse current	I _R	V _R = 50 V, T _j = 25 °C V _R = 50 V, T _j = 125 °C	5 100	5 100	5 100	5 100	µA

