
Spec Sheet

SMD Power Inductors (NR series S type)

NRS4018T151MDGJ



Features

- Item Summary 150uH±20%, 0.22A, 4.0x4.0x1.8mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 3500pcs


■ Products characteristics table

Inductance	150 uH ± 20 %
Case Size (mm)	4.0x4.0
Rated Current (max)	0.22 A
Saturation Current (max)	0.34 A
Saturation Current (typ)	0.39 A
Temperature Rise Current (max)	0.22 A
Temperature Rise Current (typ)	0.28 A
DC Resistance (max)	2.76 Ω
DC Resistance (typ)	2.3 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	5.5 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
Temperature characteristic (Inductance change)	± 20 %
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm


Recommended Land Patterns



2017.04.30

SMD Power Inductors (NR series S type)

NRS4018T151MDGJ





Inductance: 150 иΗ (test freq at 0.1MHz) DC Resistance: 2.3 / 2.76 ohm (typ/max)

340 mA (max) Saturation Current: 220 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

