


Capacitor, Film, Metallized Polypropylene, 2 uF, +/-5% Tol, -40/+85C, Power, 550 VAC



| Dimensions (mm) | | |
|-----------------|-----------|-----------|
| Symbol | Dimension | Tolerance |
| L | 42 | NOM |
| H | 45 | NOM |
| T | 30 | NOM |
| S | 25 | +/-0.2 |

| Packaging Specifications | |
|--------------------------|------|
| Package Kind: | Bulk |
| Package Quantity: | 32 |

| General Information | |
|---------------------|--------------------------|
| Supplier: | KEMET |
| Dielectric: | Metallized Polypropylene |
| Application: | Power |
| Style: | Radial Box |
| Features: | IGBT Circuit |
| RoHS: | Yes |

| Specifications | |
|-------------------------|----------------------|
| Capacitance: | 2 uF |
| Voltage: | 850 V |
| Tolerance: | +/-5% |
| Voltage AC: | 550 VAC |
| Rated Temperature: | 70C |
| Temperature Range: | -40/+85C |
| Maximum dVdT: | 758 v/us |
| Current/Ripple Current: | 36 Amps (100kHz 70C) |
| Current/Ripple Current: | 1517 Amps (Peak) |
| Resistance/ESR: | 2.1 mOhms (100kHz) |
| Inductance: | 43 nH |
| Miscellaneous: | Kemet Style A Tabs |