

Silicon Bridge Rectifier

V_{RRM} = 50 V - 1000 V
I_F = 4 A

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Types up to 1000 V V_{RRM}
- Ideal for printed circuit board
- High surge current capability
- High temperature soldering guaranteed: 250°C/ 10 seconds, 0.375(9.5mm) lead length
- Glass passivated chip junction
- High case dielectric strength

GBL Package



Mechanical Data

Case: Molded plastic body over passivated junctions
 Weight: 0.071 oz, 2 g
 Mounting position: Any
 Terminals: Plated leads, solderable per MIL-STD-750
 Method 2026 guaranteed

Maximum ratings, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	GBL005	GBL01	GBL02	GBL04	Unit
Repetitive peak reverse voltage	V _{RRM}		50	100	200	400	V
RMS reverse voltage	V _{RMS}		35	70	140	280	V
DC blocking voltage	V _{DC}		50	100	200	400	V
Continuous forward current	I _F	T _j ≤ 25 °C	4	4	4	4	A
Surge non-repetitive forward current, Half Sine Wave	I _{F,SM}	T _C = 25 °C, t _p = 8.3 ms	150	150	150	150	A
Operating temperature	T _j		-55 to 150	-55 to 150	-55 to 150	-55 to 150	°C
Storage temperature	T _{stg}		-55 to 150	-55 to 150	-55 to 150	-55 to 150	°C

Electrical characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	GBL005	GBL01	GBL02	GBL04	Unit
Diode forward voltage	V _F	I _F = 4 A, T _j = 25 °C	1.1	1.1	1.1	1.1	V
Reverse current	I _R	V _R = 50 V, T _j = 25 °C V _R = 50 V, T _j = 125 °C	5 500	5 500	5 500	5 500	μA

Thermal characteristics

Thermal resistance, junction - case	R _{thJA} R _{thJL}		22.0 3.5	22.0 3.5	22.0 3.5	22.0 3.5	°C/W
-------------------------------------	--	--	-------------	-------------	-------------	-------------	------

