

F91 Series



Low ESR, Resin-Molded Chip J-Lead



FEATURES

- Compliant to the RoHS2 directive 2011/65/EU
- SMD J-lead
- Low ESR




APPLICATIONS

- General medium power DC/DC convertors


CASE DIMENSIONS: millimeters (inches)

Code	EIA Code	EIA Metric	L	W ₁	W ₂	H	S
B	1210	3528-21	3.50 ± 0.20 (0.126 ± 0.008)	2.80 ± 0.20 (0.110 ± 0.008)	2.20 ± 0.10 (0.087 ± 0.004)	1.90 ± 0.20 (0.075 ± 0.008)	0.80 ± 0.20 (0.031 ± 0.008)
C	2312	6032-27	6.00 ± 0.20 (0.236 ± 0.008)	3.20 ± 0.20 (0.126 ± 0.008)	2.20 ± 0.10 (0.087 ± 0.004)	2.50 ± 0.20 (0.098 ± 0.008)	1.30 ± 0.20 (0.051 ± 0.008)
N	2917	7343-30	7.30 ± 0.20 (0.287 ± 0.008)	4.30 ± 0.20 (0.169 ± 0.008)	2.40 ± 0.10 (0.094 ± 0.004)	2.80 ± 0.20 (0.110 ± 0.008)	1.30 ± 0.20 (0.051 ± 0.008)

B CASE




C, N CASE




MARKING


B CASE



C CASE



N CASE



HOW TO ORDER

F91	1A	107	M	C	
Type	Rated Voltage	Capacitance Code	Tolerance	Case Size	Packaging

pF code: 1st two digits represent significant figures, 3rd digit represents multiplier (number of zeros to follow)

TECHNICAL SPECIFICATIONS

Category Temperature Range:	-55 to +125°C
Rated Temperature:	+85°C
Capacitance Tolerance:	±20%, ±10% at 120Hz
Dissipation Factor:	Refer to next page
ESR 100kHz:	Refer to next page
Leakage Current:	After 1 minute's application of rated voltage, leakage current at 20°C is not more than 0.01CV or 0.5µA, whichever is greater. After 1 minute's application of rated voltage, leakage current at 85°C is not more than 0.1CV or 5µA, whichever is greater. After 1 minute's application of derated voltage, leakage current at 125°C is not more than 0.125CV or 6.3µA, whichever is greater.
Capacitance Change By Temperature	+15% Max. at +125°C +10% Max. at +85°C -10% Max. at -55°C

F91 Series



Low ESR, Resin-Molded Chip J-Lead

CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

Capacitance μF	Code	Rated Voltage						
		4V (0G)	6.3V (0J)	10V (1A)	16V (1C)	20V (1D)	25V (1E)	35V (1V)
6.8	685							C
10	106						C	N
15	156					C		N
22	226			B			N	N
33	336			B/C	N		N	
47	476		B	N	N	N		
68	686		C					
100	107		C	C	N			
150	157	C	C	N				
220	227	C	C/N	N				
330	337	N	N	N				
470	477	N	N					
680	687	N						

Available Ratings

RATINGS & PART NUMBER REFERENCE

AVX Part No.	Case Size	Capacitance (μF)	Rated Voltage (V)	DCL (μA)	DF @ 120Hz (%)	ESR @ 100kHz (mΩ)	100kHz RMS Current (mA)	
							20°C	20°C
4 Volt								
F910G157MCC	C	150	4	6.0	12	250	663	
F910G227MCC	C	220	4	8.8	12	250	663	
F910G337MNC	N	330	4	13.2	10	100	1225	
F910G477MNC	N	470	4	18.8	16	100	1225	
F910G687MNC	N	680	4	27.2	18	100	1225	
6.3 Volt								
F910J107MCC	C	100	6.3	6.3	8	250	663	
F910J157MCC	C	150	6.3	9.5	12	250	663	
F910J227MCC	C	220	6.3	13.9	14	250	663	
F910J227MNC	N	220	6.3	13.9	10	100	1225	
F910J337MNC	N	330	6.3	20.8	14	100	1225	
F910J477MNC	N	470	6.3	29.6	16	100	1225	
10 Volt								
F911A476MBA	B	47	10	4.7	8	500	412	
F911A686MCC	C	68	10	6.8	8	300	606	
F911A107MCC	C	100	10	10.0	10	250	663	
F911A157MNC	N	150	10	15.0	10	100	1225	
F911A227MNC	N	220	10	22.0	12	100	1225	
F911A337MNC	N	330	10	33.0	18	100	1225	
16 Volt								
F911C226MBA	B	22	16	3.5	8	950	299	
F911C336MBA	B	33	16	5.3	8	950	299	
F911C336MCC	C	33	16	5.3	6	400	524	
F911C476MNC	N	47	16	7.6	6	150	1000	
F911C107MNC	N	100	16	16	10	100	1225	
20 Volt								
F911D156MCC	C	15	20	3	6	450	494	
F911D336MNC	N	33	20	6.6	6	200	866	
F911D476MNC	N	47	20	9.4	8	200	866	
25 Volt								
F911E106MCC	C	10	25	2.5	6	450	494	
F911E226MNC	N	22	25	5.5	6	200	866	
F911E336MNC	N	33	25	8.3	8	200	866	
F911E476MNC	N	47	25	11.8	8	250	775	
35 Volt								
F911V685MCC	C	6.8	35	2.4	6	600	428	
F911V106MNC	N	10	35	3.5	6	300	707	
F911V156MNC	N	15	35	5.3	6	300	707	
F911V226MNC	N	22	35	7.7	8	300	707	

* In case of capacitance tolerance ± 10% type, "K" will be put at 9th digit of type numbering system

F91 Series



Low ESR, Resin-Molded Chip J-Lead

QUALIFICATION TABLE

TEST	F91 series (Temperature range -55°C to +125°C) Condition
Damp Heat (Steady State)	At 40°C, 90 to 95% R.H., 500 hours (No voltage applied) Capacitance Change Within ±10% of the initial value Dissipation Factor Initial specified value or less Leakage Current Initial specified value or less
Temperature Cycles	-55°C / +125°C, 30 minutes each, 5 cycles Capacitance Change Within ±5% of the initial value Dissipation Factor Initial specified value or less Leakage Current Initial specified value or less
Resistance to Soldering Heat	10 seconds reflow at 260°C, 5 seconds immersion at 260°C. Capacitance Change Within ±5% of the initial value Dissipation Factor Initial specified value or less Leakage Current Initial specified value or less
Surge	After application of surge voltage in series with a 33Ω resistor at the rate of 30 seconds ON, 30 seconds OFF, for 1000 successive test cycles at 85°C, capacitors shall meet the characteristic requirements in the table above. Capacitance Change Within ±5% of the initial value Dissipation Factor Initial specified value or less Leakage Current Initial specified value or less
Endurance	After 2000 hours' application of rated voltage in series with a 3Ω resistor at 85°C, or derated voltage in series with a 3Ω resistor at 125°C, capacitors shall meet the characteristic requirements in the table above. Capacitance Change Within ±10% of the initial value Dissipation Factor Initial specified value or less Leakage Current Initial specified value or less
Shear Test	After applying the pressure load of 5N for 10±1 seconds horizontally to the center of capacitor side body which has no electrode and has been soldered beforehand on a substrate, there shall be found neither exfoliation nor its sign at the terminal electrode.
Terminal Strength	Keeping a capacitor surface-mounted on a substrate upside down and supporting the substrate at both of the opposite bottom points 45mm apart from the center of capacitor, the pressure strength is applied with a specified jig at the center of substrate so that the substrate may bend by 1mm as illustrated. Then, there shall be found no remarkable abnormality on the capacitor terminals.

