


**Phase leg Series & SiC parallel diodes
Super Junction MOSFET Power Module**

**V_{DSS} = 800V
R_{DSon} = 75mΩ max @ T_j = 25°C
I_D = 56A @ T_c = 25°C**



Application


- Motor control
- Switched Mode Power Supplies
- Uninterruptible Power Supplies

Features

- **CoolMOS™**
 - Ultra low R_{DSon}
 - Low Miller capacitance
 - Ultra low gate charge
 - Avalanche energy rated
- **Parallel SiC Schottky Diode**
 - Zero reverse recovery
 - Zero forward recovery
 - Temperature Independent switching behavior
 - Positive temperature coefficient on VF
- Kelvin source for easy drive
- Very low stray inductance
 - Symmetrical design
 - M5 power connectors
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Low profile
- RoHS Compliant



All ratings @ T_j = 25°C unless otherwise specified

Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V _{DSS}	Drain - Source Breakdown Voltage	800	V
I _D	Continuous Drain Current	T _c = 25°C T _c = 80°C	56 43
I _{DM}	Pulsed Drain current		
V _{GS}	Gate - Source Voltage	±30	V
R _{DSon}	Drain - Source ON Resistance	75	mΩ
P _D	Maximum Power Dissipation	T _c = 25°C	568
I _{AR}	Avalanche current (repetitive and non repetitive)		
E _{AR}	Repetitive Avalanche Energy	0.5	mJ
E _{AS}	Single Pulse Avalanche Energy	670	

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I _{DSS}	Zero Gate Voltage Drain Current	V _{GS} = 0V, V _{DS} = 800V	T _j = 25°C			100
		V _{GS} = 0V, V _{DS} = 800V	T _j = 125°C			1000
R _{DS(on)}	Drain – Source on Resistance	V _{GS} = 10V, I _D = 28A			75	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} = V _{DS} , I _D = 4mA	2.1	3	3.9	V
I _{GSS}	Gate – Source Leakage Current	V _{GS} = ±20 V, V _{DS} = 0V			±200	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C _{iss}	Input Capacitance	V _{GS} = 0V V _{DS} = 25V f = 1MHz		9015		pF
C _{oss}	Output Capacitance			4183		
C _{rss}	Reverse Transfer Capacitance			215		
Q _g	Total gate Charge	V _{GS} = 10V V _{Bus} = 400V I _D = 56A		364		nC
Q _{gs}	Gate – Source Charge			48		
Q _{gd}	Gate – Drain Charge			184		
T _{d(on)}	Turn-on Delay Time		10			ns
T _r	Rise Time	V _{GS} = 15V V _{Bus} = 533V I _D = 56A	13			
T _{d(off)}	Turn-off Delay Time		83			
T _f	Fall Time		35			
E _{on}	Turn-on Switching Energy	Inductive switching @ 25°C V _{GS} = 15V, V _{Bus} = 533V I _D = 56A, R _G = 1.2Ω	583			μJ
E _{off}	Turn-off Switching Energy		556			
E _{on}	Turn-on Switching Energy		1020			μJ
E _{off}	Turn-off Switching Energy	Inductive switching @ 125°C V _{GS} = 15V, V _{Bus} = 533V I _D = 56A, R _G = 1.2Ω	684			
R _{thJC}	Junction to Case Thermal Resistance				0.22	°C/W

Series diode ratings and characteristics


Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit	
V _{RRM}	Maximum Peak Repetitive Reverse Voltage		1000			V	
I _{RM}	Maximum Reverse Leakage Current	V _R =1000V			300	μA	
I _F	DC Forward Current		T _c = 80°C	120		A	
V _F	Diode Forward Voltage	I _F = 120A		1.9	2.5	V	
		I _F = 240A		2.2			
		I _F = 120A	T _j = 125°C	1.7			
t _{rr}	Reverse Recovery Time	I _F = 120A V _R = 667V di/dt = 400A/μs	T _j = 25°C	280		ns	
			T _j = 125°C	350			
Q _{rr}	Reverse Recovery Charge		T _j = 25°C	1.52		μC	
			T _j = 125°C	7.2			
R _{thJC}	Junction to Case Thermal Resistance				0.46	°C/W	






Parallel diode ratings and characteristics







Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V _{RRM}	Maximum Peak Repetitive Reverse Voltage			1200			V
I _{RM}	Maximum Reverse Leakage Current	V _R =1200V	T _j = 25°C		300	1200	µA
			T _j = 175°C		600	6000	
I _F	DC Forward Current		T _c = 100°C		30		A
V _F	Diode Forward Voltage	I _F = 30A	T _j = 25°C		1.6	1.8	V
			T _j = 175°C		2.6	3.0	
Q _C	Total Capacitive Charge	I _F = 30A, V _R = 1200V di/dt = 1600A/µs			168		nC
Q	Total Capacitance	f = 1MHz, V _R = 200V			270		pF
		f = 1MHz, V _R = 400V			198		
R _{thJC}	Junction to Case Thermal Resistance				0.45		°C/W







Thermal and package characteristics

Symbol	Characteristic		Min	Max	Unit
V _{ISOL}	RMS Isolation Voltage, any terminal to case t=1 min, 50/60Hz		4000		V
T _J	Operating junction temperature range		-40	150	°C
T _{JOP}	Recommended junction temperature under switching conditions		-40	T _{Jmax} -25	
T _{STG}	Storage Temperature Range		-40	125	
T _C	Operating Case Temperature		-40	100	
Torque	Mounting torque	To heatsink	M6	3	N.m
		For terminals	M5	2	
Wt	Package Weight			300	g




SP6 Package outline (dimensions in mm)

 See application note APT0601 - Mounting Instructions for SP6 Power Modules on www.microsemi.com

Typical CoolMOS Performance Curve






Typical SiC Diode Performance Curve



"COOLMOS™ comprise a new family of transistors developed by Infineon Technologies AG. "COOLMOS" is a trademark of Infineon Technologies AG".

DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.