344/348 Series Blown Fuse Indicating / Low Profile Holders for 3AB/3AG Fuses









Dimensions

344 Series





Additional Information



Datasheet 344 Series



Datasheet 348 Series



344 Series



Resources 348 Series



Samples 344 Series



Samples 348 Series

Product Characteristics				
Compatible Fuses	For 3AB/3AG Type Fuses			
Features	Low profile design Blown fuse indicator			
Electrical	348 Series: Rated at 15 amps for any voltage up to 250 volts. 344 Series: Rated at 15 amps at lamp voltage shown below.			
Dielectric Strength	1500 volts minimum. When designing indicating type fuseholders into a circuit, consideration should be given to the resistance of fractional amperage fuses and the parallel resistance of the indicator lamp and its resistor.			
Mounting	Panel thickness range: .031" through .125".			
Molded Parts	Black thermoplastic body (UL94 V-0). Thermoplastic bezel, cap and lens (UL94 V-2). See tables below fo colors.			
Terminals	Brass. Tin-plated.			
Ambient Temperature	Non-indicating: –40°C to +85°C. Indicating: –40°C to +60°C.			
Fuse Installation	Insert a fuse into the cap and push the assembly into the body until it latches. Press in and down to unlatch for removal.			

NOTE: Ensure that proper re-rating is factored in fuseholder selection.

Ordering Information

Catalog Number 3/16" Q.C. 1/4" Q.Terminals Termin	.C. Lam		Lamp Current	Resistor	Lens Color
344 601 344 8	01 Incand	i h	40 ma	No	Amber
344 602 344 8	02 Incand	1 14	80 ma	No	Amber
344 603 344 8	03 Incand	- 1 78	40 ma	No	Amber
344 604 344 8	04 Neor	n 120	1.2 ma	Yes	Clear
344 605 344 8	05 Neor	n 240	.3 ma	Yes	Clear

Standard Body and Bezel color is black. Other Bezel colors may be available as special order. Please contact Littelfuse for additional information and detailed arrangements.

Catalog Number 3/16" Q.C. 1/4" Q.C. Terminals Terminals		Bezel Color	Cap Color	
348 671	348 871	Black	Red	
348 677	348 877	Black	Black	

NOTE:

Standard Body and Bezel color is black. Other Bezel and Cap colors may be available as special order. Please contact Littelfuse for additional information and arrangments