# **PREO Power Line EMI Filters**

# **Series HB**

A Division of Eastek International Corporation







UL Recognized CSA Certified VDE Approved

# Introduction

The HB series are general purpose EMI filters specially designed for medical and dental equipment, both patient care and nonpatient categories. The leakage current in this series is extremely low to satisfy the stringent leakage current limit imposed by safety regulations for medical and dental equipment, such as UL544 and IEC601.

#### Minimum Insertion Loss in dB


Common mode (line to ground) in 50 ohm system:

MODEL	Frequency in MHz								
	0.05	0.10	0.15	0.50	1.0	5.0	10	30	
06HB11/33/M1	3	7	11	20	22	24	22	18	

Differential mode (line to line) in 50 ohm system:

	Frequency in MHz									
MODEL	0.10	0.15	0.50	1.0	3.0	5.0	10	30		
06HB11/33/M1	3	6	14	20	30	35	35	35		

### **Schematic**



## **Electrical ratings**

Maximum operating voltage:

Operating frequency: 50/60 Hz

Hipot rating (one minute):

Line to Ground: 1500 VAC Line to Line: 1450 VDC

Maximum leakage current (each line to ground):

@ 120 VAC / 60 Hz:

2 µA

250 VAC

@ 250 VAC / 50 Hz:

5 μΑ

Rated current at 40°C ambient temperature:

06HB11, 06HB33, 06HBM1

6 A

Now in Stock at

#### **EASTEK INTERNATIONAL CORPORATION**

114 Joey Drive, Elk Grove, IL 60007, USA Phone: 847 437 2800 Fax: 847 437 2809

or your local agent