

## 1N4148 (LL4148) FAST SWITCHING DIODE


**Features:**

- Fast Switching Speed
- Glass Package Version for High Reliability
- High Conductance
- Available in Both Through-Hole and Surface Mount Versions
- This is a Pb – Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request


**Mechanical Data:**

- Case: DO-35, Mini MELF/DL-35
- Terminals: Plated leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode band
- Weight: DO-35 0.13 grams  
Mini MELF/DL-35 0.05 grams
- Marking: Cathode band

**Mechanical Dimensions: In mm/Inches**



**1N4148**



**LL4148**

DO-35				
Dim	Min	Max	Min	Max
A	25.40	—	1.000	—
B	—	4.00	—	0.157
C	—	0.60	—	0.024
D	—	2.00	—	0.079
	in mm		In inch	

**DO-35**

MiniMELF				
Dim	Min	Max	Min	Max
A	3.30	3.70	0.130	0.146
B	1.30	1.60	0.051	0.063
C	0.28	0.50	0.011	0.020
	In mm		In inch	

**Mini MELF/DL-35**

**Ordering Information:**

Device	Package	Shipping
1N4148	DO-35 (Pb-Free)	5000pcs /reel
LL4148	Mini MELF/DL-35 (Pb-Free)	2500pcs / reel

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification.



**Maximum Ratings @ $T_A=25^{\circ}\text{C}$  unless otherwise specified**

Characteristic	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	$V_{RM}$	100	V
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	$V_{RRM}$ $V_{RWM}$ $V_R$	75	V
RMS Reverse Voltage	$V_{R(RMS)}$	53	V
Forward Continuous Current (Note 1)	$I_{FM}$	300	mA
Rectified Current(Average), Half Wave Rectification with Resistive Load and $f \geq 50\text{MHz}$ (Note 1)	$I_O$	150	mA
Non-Repetitive Peak Forward Surge Current @ $t=1.0\text{s}$ @ $t=1.0\mu\text{s}$	$I_{FSM}$	1.0 2.0	A
Power Dissipation(Note 1) Derate Above $25^{\circ}\text{C}$	$P_D$	500 1.68	mW mW/ $^{\circ}\text{C}$
Thermal Resistance, Junction to Ambient Air(Note 1)	$R_{\theta JA}$	300	$^{\circ}\text{C}/\text{W}$
Junction and Storage Temperature Range	$T_J, T_{STG}$	-65 to +175	$^{\circ}\text{C}$

**Electrical Characteristics** @ $T_A=25^{\circ}\text{C}$  unless otherwise specified

Characteristic	Symbol	Min	Max	Unit	Test Condition
Forward Voltage	$V_{FM}$	-	1.0	V	@ $I_F=10\text{mA}$
Peak Reverse Current	$I_{RM}$	-	5.0 50 30 25	$\mu\text{A}$ $\mu\text{A}$ $\mu\text{A}$ nA	@ $V_R=75\text{V}$ @ $V_R=70\text{V}, T_J=150^{\circ}\text{C}$ @ $V_R=20\text{V}, T_J=150^{\circ}\text{C}$ @ $V_R=20\text{V}$
Capacitance	$C_j$	-	4.0	pF	$V_R=0\text{V}, f=1.0\text{MHz}$
Reverse Recovery Time	$t_{rr}$	-	4.0	ns	$I_F=10\text{mA}$ to $I_R=1.0\text{mA}$ $V_R=6.0\text{V}, R_L=100\Omega$

Note: 1. Diode on Ceramic substrate 10×8×0.7mm





1N4148 (LL4148)

**Technical Data**  
**Data Sheet N0230, Rev. -**

***Green Products***

**DISCLAIMER:**

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC - Sangdest Microelectronics (Nanjing) Co., Ltd sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC - Sangdest Microelectronics (Nanjing) Co., Ltd assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC - Sangdest Microelectronics (Nanjing) Co., Ltd be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC - Sangdest Microelectronics (Nanjing) Co., Ltd.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..