

**KEMET Part Number: PHE840MF7330MF16R06L2**  
(F840FV335M275C)

Film, Metallized Polypropylene, Safety, PHE840M/F840, 3.3 uF, 20%, 760 V, 275 V, 105C, Lead Spacing = 27.5mm



General Information	
<b>Dielectric:</b>	Metallized Polypropylene
<b>Style:</b>	Radial
<b>Series:</b>	PHE840M/F840
<b>Features:</b>	Pulse
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads
<b>Approvals:</b>	ENEC, UL, cUL
<b>Miscellaneous:</b>	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Dimensions	
<b>L</b>	31.5mm MAX
<b>H</b>	30mm MAX
<b>T</b>	21mm MAX
<b>S</b>	27.5mm +/-0.4mm
<b>LL</b>	6mm NOM
<b>F</b>	0.8mm NOM

Specifications	
<b>Capacitance:</b>	3.3 uF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage DC:</b>	760 VDC
<b>Voltage AC:</b>	275 VAC
<b>Temperature Range:</b>	-55/+105C
<b>Rated Temperature:</b>	105C
<b>Dissipation Factor:</b>	0.1% 1kHz, 0.8% 10kHz
<b>Insulation Resistance:</b>	3.0303 GOhms
<b>Max dVdt:</b>	100 V
<b>Safety Class:</b>	X2

Packaging Specifications	
<b>Packaging:</b>	Bulk, Tray
<b>Packaging Quantity:</b>	108